



SAFETY DATA SHEET
RonaDeck Resin Bound Surfacing - Part A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RonaDeck Resin Bound Surfacing - Part A
Product number PC344

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen) [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) [ERC5] Industrial use resulting in inclusion into or onto a matrix. [AC4] Stone, plaster, cement, glass and ceramic articles. Adhesive. Sealant.

1.3. Details of the supplier of the safety data sheet

Supplier Ronacrete Limited
 Ronac House
 Flex Meadow
 Harlow
 Essex
 CM19 5TD
 www.ronacrete.co.uk
 Tel: 01279 638 700
 Fax: 01279 638 701
 email: sds@ronacrete.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 1279 638700

National emergency telephone number UK Consumers NHS 111. Medical professionals - www.toxbase.org

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
Health hazards Elicitation - EUH208
Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) R52/53

2.2. Label elements

Hazard statements EUH208 Contains Dibutyltin dilaurate. May produce an allergic reaction.
 H412 Harmful to aquatic life with long lasting effects.

RonaDeck Resin Bound Surfacing - Part A

Precautionary statements	P273 Avoid release to the environment.
	P501 Dispose of contents/container in accordance with national regulations.
	P202 Do not handle until all safety precautions have been read and understood.
	P270 Do not eat, drink or smoke when using this product.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

n-butyl-2-(1-ethylpentyl)-1,3-oxazolidine	1-5%
CAS number: 165101-57-5 EC number: 425-660-0 REACH registration number: 01-0000017206-75-XXXX	
Classification Aquatic Chronic 2 - H411	
Dibutyltin dilaurate	<1%
CAS number: 77-58-7 EC number: 201-039-8 REACH registration number: 01-2119496068-27-XXXX	
M factor (Chronic) = 1	
Classification Skin Corr. 1A - H314 Eye Dam. 1 - H318 Skin Sens. 1B - H317 Muta. 2 - H341 Repr. 1B - H360FD STOT SE 1 - H370 STOT RE 1 - H372 Aquatic Chronic 1 - H410	
2-methoxy-1-methylethyl acetate	<1%
CAS number: 108-65-6 EC number: 203-603-9	
Classification Flam. Liq. 3 - H226	
n-butyl acetate	<1%
CAS number: 123-86-4 EC number: 204-658-1	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT SE 3 - H336	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

RonaDeck Resin Bound Surfacing - Part A

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.
Ingestion	Do not induce vomiting. Get medical attention. Show this Safety Data Sheet to the medical personnel.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	May cause sensitisation by skin contact.
Eye contact	May irritate eyes. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Toxic gases or vapours.
--------------------------------------	-------------------------

5.3. Advice for firefighters

Protective actions during firefighting	No action shall be taken without appropriate training or involving any personal risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes and clothing.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Dangerous for the environment if discharged into watercourses. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with non-combustible, absorbent material. Place waste in labelled, sealed containers.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For waste disposal, see Section 13.
------------------------------------	-------------------------------------

SECTION 7: Handling and storage

RonaDeck Resin Bound Surfacing - Part A

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Dibutyltin dilaurate

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³

Short-term exposure limit (15-minute): WEL 0.2 mg/m³

2-methoxy-1-methylethyl acetate

Long-term exposure limit (8-hour TWA): WEL 274 mg/m³

Short-term exposure limit (15-minute): WEL 548 mg/m³

n-butyl acetate

Long-term exposure limit (8-hour TWA): WEL 724 mg/m³

Short-term exposure limit (15-minute): WEL 966 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Take off contaminated clothing and wash it before reuse.

Respiratory protection

Disposable filtering half mask respirators should comply with European Standard EN149 or EN405.

Environmental exposure controls

Keep container tightly sealed when not in use. Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Viscous liquid.

Colour Yellow.

RonaDeck Resin Bound Surfacing - Part A

Odour	Mild.
Initial boiling point and range	260-300°C @ 101325 Pa
Relative density	0.9 - 1.0 @ 20°C

9.2. Other information

Other information	None.
-------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
------------------------------------	-------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents.
--------------------	--------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Carbon dioxide (CO ₂). Carbon monoxide (CO).
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin contact	The product contains a sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals. In the event of any sensitisation symptoms developing, ensure further exposure is avoided.
--------------	---

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity	Harmful to aquatic life with long lasting effects.
----------	--

12.2. Persistence and degradability

Persistence and degradability	The degradability of the product is not known.
-------------------------------	--

12.3. Bioaccumulative potential

Bioaccumulative potential	Immiscible with water.
---------------------------	------------------------

12.4. Mobility in soil

Mobility	Not known.
----------	------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	No data available.
------------------------------------	--------------------

RonaDeck Resin Bound Surfacing - Part A

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods For quantities up to 5 kg of Part A, mix with an equal amount of Part B. Heat will evolve from this mixture, so pour onto aggregate to increase surface area and allow to harden. Do not leave the mixture in the container for longer than 5 minutes. Where there is an excess of Part A or Part B that cannot be reacted off, this must be disposed of by a licensed waste disposal company in accordance with national guidelines. All containers must be properly labelled and a Safety data sheet provided for the waste disposal company.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

RonaDeck Resin Bound Surfacing - Part A

EU legislation	<p>Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 18 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).</p>
Guidance	<p>www.echa.europa.eu www.hse.gov.uk Workplace Exposure Limits EH40. Supplier product information and safety data sheets.</p>

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by	sds@ronacrete.co.uk
Revision date	26/03/2015
Revision	1
SDS number	4579
Hazard statements in full	<p>EUH208 Contains Dibutyltin dilaurate. May produce an allergic reaction. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H341 Suspected of causing genetic defects. H360FD May damage fertility. May damage the unborn child. H370 Causes damage to organs . H372 Causes damage to organs through prolonged or repeated exposure. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET
RonaDeck Resin Bound Surfacing - Part B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RonaDeck Resin Bound Surfacing - Part B

Product number PC344

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen) [ERC5] Industrial use resulting in inclusion into or onto a matrix [AC4] Stone, plaster, cement, glass and ceramic articles. [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) Adhesive. Sealer.

1.3. Details of the supplier of the safety data sheet

Supplier Ronacrete Limited
 Ronac House
 Flex Meadow
 Harlow
 Essex
 CM19 5TD
 www.ronacrete.co.uk
 Tel: 01279 638 700
 Fax: 01279 638 701
 email: sds@ronacrete.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 1279 638700

National emergency telephone number UK Consumers NHS 111. Medical professionals - www.toxbase.org

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Elicitation - EUH208 Skin Sens. 1 - H317 STOT SE 3 - H335 STOT SE 3 - H335

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xn; R20. Xi; R37. R43

2.2. Label elements

RonaDeck Resin Bound Surfacing - Part B

Pictogram



Signal word

Warning

Hazard statements

H317 May cause an allergic skin reaction.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing vapour/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with national regulations.

Contains

Hexamethylene diisocyanate oligomers, Isocyanurate, hexamethylene-di-isocyanate

2.3. Other hazards

Reacts with water.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hexamethylene diisocyanate oligomers, Isocyanurate	60-100%
---	----------------

CAS number: 28182-81-2

REACH registration number: 01-
2119485796-17-XXXX

Classification

Acute Tox. 4 - H332
 Skin Sens. 1 - H317
 STOT SE 3 - H335
 STOT SE 3 - H335

RonaDeck Resin Bound Surfacing - Part B

hexamethylene-di-isocyanate	<1%
CAS number: 822-06-0	EC number: 212-485-8
Classification Acute Tox. 3 - H331 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 STOT SE 3 - H335 STOT SE 3 - H335	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing stops, provide artificial respiration. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention. Show this Safety Data Sheet to the medical personnel.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.
Protection of first aiders	Care should be taken to avoid contact with contaminants when removing contaminated clothing. Wear suitable gloves.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	A single exposure may cause the following adverse effects: General respiratory distress, unproductive cough. May cause respiratory system irritation.
Ingestion	May cause discomfort if swallowed.
Skin contact	May cause sensitisation by skin contact.
Eye contact	Symptoms following overexposure may include the following: Pain or irritation. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Water.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Toxic gases or vapours.
-------------------------	-------------------------

RonaDeck Resin Bound Surfacing - Part B

5.3. Advice for firefighters

Protective actions during firefighting Evacuate area. Do not allow water to contact any leaked material.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Control run-off water by containing and keeping it out of sewers and watercourses.

6.4. Reference to other sections

Reference to other sections For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions For personal protection, see Section 8. Read label before use. Do not allow contact with water. Avoid inhalation of vapours. Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a demarcated bunded area to prevent release to drains and/or watercourses. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hexamethylene diisocyanate oligomers, Isocyanurate

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³ as -NCO

Short-term exposure limit (15-minute): WEL 0.07 mg/m³ as -NCO

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

RonaDeck Resin Bound Surfacing - Part B

Eye/face protection	Wear tight-fitting, chemical splash goggles or face shield.
Hand protection	Wear protective gloves made of the following material: Rubber (natural, latex).
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Provide eyewash station. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Colourless to pale yellow liquid.
Odour	No characteristic odour.
Melting point	< -20°C
Initial boiling point and range	>220°C @ 1.33 hPa
Flash point	137°C
Relative density	1.16 @ 25°C
Viscosity	2400 mPa s @ 25°C

9.2. Other information

Other information	None.
--------------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Reacts with water. Alcohols. Alkalis. Amines.
-------------------	---

10.2. Chemical stability

Stability	Stable under the prescribed storage conditions.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Contact with water liberates toxic gas. Carbon dioxide (CO ₂).
---	--

10.4. Conditions to avoid

Conditions to avoid	Contact with water liberates carbon dioxide causing an increase of pressure inside containers. This may result in containers exploding.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Never add water to this product.
---------------------------	----------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Carbon dioxide (CO ₂). Toxic gases or vapours.
---	--

SECTION 11: Toxicological information

RonaDeck Resin Bound Surfacing - Part B

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 1,507.53768844

ATE inhalation (dusts/mists mg/l) 1.50314157

Inhalation	Harmful by inhalation. A single exposure may cause the following adverse effects: General respiratory distress, unproductive cough. Upper respiratory irritation.
Ingestion	The product is considered to be a low hazard under normal conditions of use. Get medical attention if a large quantity has been ingested.
Skin contact	The product contains a sensitising substance. In the event of any sensitisation symptoms developing, ensure further exposure is avoided.
Eye contact	May cause eye irritation.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity The product components are not classified as environmentally hazardous.

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods For quantities up to 5 kg of Part A, mix with an equal amount of Part B. Heat will evolve from this mixture, so pour onto aggregate to increase surface area and allow to harden. Do not leave the mixture in the container for longer than 5 minutes. Where there is an excess of Part A or Part B that cannot be reacted off, this must be disposed of by a licensed waste disposal company in accordance with national guidelines. All containers must be properly labelled and a Safety data sheet provided for the waste disposal company.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

RonaDeck Resin Bound Surfacing - Part B

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Dangerous Preparations Directive 1999/45/EC.
 Dangerous Substances Directive 67/548/EEC.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Guidance www.echa.europa.eu
www.hse.gov.uk
 Supplier product information and safety data sheets.
 Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by sds@ronacrete.co.uk
Revision date 09/04/2015
Revision 1
SDS number 4585

RonaDeck Resin Bound Surfacing - Part B

Risk phrases in full

R20 Harmful by inhalation.
R23 Toxic by inhalation.
R36/37/38 Irritating to eyes, respiratory system and skin.
R37 Irritating to respiratory system.
R42/43 May cause sensitisation by inhalation and skin contact.
R43 May cause sensitisation by skin contact.

Hazard statements in full

EUH208 Contains hexamethylene-di-isocyanate. May produce an allergic reaction.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.